



FINISHLINE TILE GROUT/PUTTY



Ready to use
Self curing
Anti cracking
Smooth appearance
Mould & stain resistant
High adhesion strength

**+
PROS**

Coverage

1 kg of grout will cover approximately 2.5 m² at 1.5 mm joints. Coverage is dependent on tile dimensions and joint width can be calculated using the formula below.

$$\frac{(\text{Tile Length} + \text{Tile Breadth}) \times \text{Tile Thickness} \times \text{Joint Width} \times \text{Specific Gravity}}{(\text{Tile Length} + \text{Joint Width}) \times (\text{Tile Breadth} + \text{Joint Width})} = \text{Kg/m}^2$$

Usage Instructions

1. Wait for at least 24 hours after tiles installation to apply the grout.
2. Mix 350 ml clean water to 1 kg Mix&Fix Finishline to prepare a homogeneous paste.
3. Clean the tiles joints thoroughly before application.
4. Apply the prepared grout paste at the tiles joints.
5. Tool the grout joints.
6. Wait for an hour or till the grout hardens, then use a clean cloth to wipe the tiles.



CEMENTITIOUS TILE JOINT FILLER

Finishline is a specially formulated grout for filling joints between tiles and natural stone installations. It consists of binding materials, premium grade additives, polymers, and fillers.

Used For

All types of tiles, marble, granite and sanitary wares

Application Areas

- ▶ Walls
- ▶ Floors
- ▶ Kitchens
- ▶ Bathrooms
- ▶ Swimming pools

**EXTERIOR
&
INTERIOR**

Quality Standards

Conforms to ANSI A108.4 & ANSI A118.7

Pack Size	Shelf Life	Storage
1 kg	12 months	Store in a cool & dry area

Technical Data

Appearance	Different colors
Setting time	12 hrs
Pot Life	30 - 60 min
Final drying time	24 hrs @ 20°C & 50% humidity

Manufactured by



BMC INDUSTRIES LTD.

A Mozid Tower, Ka-24, Pragati Sarani, Kuril, Vatara
Dhaka-1229, Bangladesh
☎ 01313 444 650 ✉ bmc.com.bd@gmail.com



**COUNTRIES OF
INGREDIENTS
ORIGIN**

